



AMAC
AMERICAN MANUFACTURING AND COMPONENTS

PRE-OPERATION INSPECTION CHECKLIST

Shuttle Car · Daily Operator Check

Before you start: park on stable, level ground, wear required PPE, and secure the machine. Do not operate if any item fails or fluid is below spec.

WALK-AROUND INSPECTION

☐	Fluid leaks
☐	Damaged hoses or fittings
☐	Loose hardware
☐	Structural cracks
☐	Missing guards or panels
☐	Tire condition and inflation
☐	Debris in wheel wells / engine bay
☐	All access doors latched

GREASE POINTS

☐	Wheel well frame pins and pivots
☐	Boom pivot locations
☐	Cab slide plate assembly

ELECTRICAL

☐	Battery disconnect engaged
☐	Breakers and strobe switch OK

FLUID LEVELS

☐	Engine oil (red-handle dipstick)
☐	Pump drive oil (pump pad)
☐	Hydraulic oil (sight glass)
☐	Engine coolant (both sight glasses)
☐	DEF (display / blue cap)
☐	Fuel (sight glasses / display)

PRE-START AND BRAKE CHECK

☐	Machine on level ground
☐	Main Power ON, brake depressed
☐	Engine running (green light)
☐	Brake pressure 250+ PSI (green)
☐	Steering mode verified

FILTERS (per schedule)

☐	Air filter
☐	Engine oil filter
☐	Hydraulic filters
☐	Emergency pump filter
☐	DEF filter